

MODEL		RAYZR 7 200 DAYLIGHT	ARRI® L7-D TUNEABLE	Desisti F10	Litepanels Sola 9™
LED SOURCE					
Color Rendition	▶	TLCI 95 ~ 98, CRI 92 ~ 96	CRI Average > 92	CRI higher than 95	TLCI 94
Beam Angle		18° - 50° (Half Peak Angle)	15° to 50° (Half Peak Angle)	12° to 54° (Half Peak Angle)	14° to 53° (Half Peak Angle)
White Light		Daylight 5,600 K	5,000 - 6,500 K Continuously Variable CCT	Daylight 5,600K	Daylight 6,545 K
POWER SUPPLY					
Operating Voltage	DC	▶ 24 - 36 V DC	N/A	N/A	N/A
	AC	90 - 264 V AC	100 - 250 V AC	120 V AC / 230 V AC	100 - 240 V AC
Power Consumption		204 W Nominal, 223 W Maximum	180 W Nominal, 220 W Maximum	250 W	190 W Maximum
AC Power Connection		power CON TRUE1	Bare Ends / Schuko / Edison Connector	power CON TRUE1	N/A
DC Power Connection		speak ON NL2MP	N/A	N/A	N/A
DIMENSIONS					
Fresnel Lens	▶	6.7" / 170mm	6.88" / 175 mm	10" / 250 mm	9" / 228.6 mm
Net Weight	▶	6.4 kg [14.1 lbs]	10.9 kg [24.0 lbs]	15.0 kg [33.0 lbs]	7.53 kg [16.6 lbs]
PHOTOMETRICS					
5600K, 30° @ 3m	▶	4409 lx / 410 fc	2444 lx / 227 fc	* 5184 lx / 482 fc	* 3700 lx / 344 fc
5600K, 30° @ 5m		1587 lx / 148 fc	880 lx / 82 fc	* 1867 lx / 173 fc	* 1332 lx / 124 fc
5600K, 30° @ 7m		810 lx / 75 fc	449 lx / 42 fc	* 953 lx / 89 fc	* 680 lx / 63 fc
				* These photometrics are converted by: "14570 lx @ 3m 12°" & "2247 lx @ 3m 54°"	* These photometrics are converted by: "8407 lx @ 3m 14°" & "1627 lx @ 3m 53°"
RETAIL PRICE	▶	\$ 989 € 939	\$ 2,872 - B&H € 2,240 - trendco.de	\$ 3,438 - B&H € 3,370 - fairlight.nl	\$ 3,150 - litepanels.com € 3,317 - litepanels.com

Arri L7-DT data from <http://www.arri.com> & Arri Photometrics APP; Desisti F10 data from <http://www.desisti.it>; Litepanels Sola 12 data from <http://www.litepanels.com>.
 "N/A" = Data not available for above mentioned resources.
 All prices Excl. VAT.